



## IDENTIFICATION

CORE



CORE PRODUCT LINE: Engineered and manufactured by Tactical Electronics

### FEATURES:

- > Receives High-Definition 1280x720p Color Video on a 5.0in IPS LCD
- > Secure pairing with multiple CORE Cameras
- > Capacitive touchscreen for setup/configuration
- > 1mm Corning Gorilla Glass screen
- > Remote Camera Control for view selection and illumination/dimming
- > Wireless Video Transmission - 5 GHz
- > AES Encryption
- > WPA2-PSK Authentication
- > Hardwire video option
- > Backlit push buttons

## DESCRIPTION

The CORE Monitor presents high-definition video from all CORE cameras over an AES encrypted 5 GHz wireless channel. The display screen is 5.0 inches and made of 1mm Gorilla Glass to provide extra durability and sunlight readable capability. When viewing video from a CORE Camera with thermal fusion technology, the CORE Monitor allows remote selection of the current view or thermal view with a single button press. Additionally, the camera's illumination can be enabled, disabled, or dimmed via the monitor's rotary wheel. The CORE Monitor features both backlit push buttons for critical, real-time controls, and a capacitive touch screen for pairing multiple CORE Cameras. An optional hardwire cable connection is available for RF-restricted environments. Attach the CORE monitor to your wrist with our secure Velcro strap or use as a handheld monitor.



**EPE**  
Trusted to Protect

Ph: +61 (0) 7 3308 9300  
Email: sales@epequip.com  
www.epequip.com

DOCUMENT : OFFICIAL SPECIFICATIONS SHEET

\*PROPRIETARY\*

COPYRIGHT : ©2018 TACTICAL ELECTRONICS AND  
MILITARY SUPPLY, LLC.

PAGE NUMBER : PRODUCT

SPECIFICATIONS AND  
INFORMATION ARE SUBJECT TO  
CHANGE WITHOUT NOTICE.

1

# CORE MONITOR

SPEC SHEET

CORE LINE  
PRODUCT



## SPECIFICATIONS

<b>MONITOR WEIGHT:</b>	14oz / 0.40kg
<b>DIMENSIONS:</b>	L 5.57in x W 3.85in x D 1.85in / L 141mm x W 98mm x D 47mm
<b>POWER SUPPLY:</b>	Three CR123 batteries
<b>RUNTIME:</b>	2.5 hours
<b>HOUSING MATERIAL:</b>	Polycarbonate+PBT (Valox 357U) and 6061-T6 Aluminum
<b>OPERATING TEMPERATURE:</b>	-4°F to 122°F
<b>OPERATING TEMPERATURE (METRIC):</b>	-20°C to 50°C
<b>FREQUENCY RANGE:</b>	5 GHz (Worldwide Availability)
<b>WIRELESS ENCRYPTION:</b>	128-bit AES Encryption with WPA2-PSK Authentication
<b>TRANSMISSION DISTANCE:</b>	650ft, Line of Sight / 200m, Line of Sight
<b>COMPATIBLE CAMERAS:</b>	CORE Pole Camera / CORE Under Door Camera / CORE Flex Camera / CORE Articulating Scope
<b>MONITOR DIAGONAL SIZE:</b>	5.0 inches
<b>MONITOR RESOLUTION:</b>	1280 x 720px
<b>MONITOR VIEWING ANGLE:</b>	80 degrees in all directions
<b>CAMERA REMOTE CONTROLS:</b>	Camera/View selection / Illumination, 0-100% dimmable
<b>HEADPHONE JACK:</b>	2.5mm, 4-conductor



Ph: +61 (0) 7 3308 9300  
Email: sales@epequip.com  
www.epequip.com

**DOCUMENT :** OFFICIAL SPECIFICATIONS SHEET

\*PROPRIETARY\*

**COPYRIGHT :** ©2018 TACTICAL ELECTRONICS AND  
MILITARY SUPPLY, LLC.

**PAGE NUMBER :** PRODUCT

SPECIFICATIONS AND  
INFORMATION ARE SUBJECT TO  
CHANGE WITHOUT NOTICE.

2